



3316 Kirkwood Highway
Wilmington, DE 19808

38016 Fenwick Blvd. Unit 3
Selbyville, DE 19975

Directions for Measuring Vertical Blinds, Sliding Panels, & Sheer Verticals

For Outside Mount

Using a steel tape to measure the exact height and width of the area to be covered.

Room Location:	
Measure Area to be Covered	Inches
Measure Width of Window/Door: (Add 4" on each side to ensure privacy and eliminate light gap.)	
For height, measure from a point 2 1/2 inches above the window trim to either the sill or floor:	
Measure the area available for stackback: (Window coverings associate will compute stackback needed to determine how your blinds will clear the window/door opening.)	

Room Location:	
Measure Area to be Covered	Inches
Measure Width of Window/Door: (Add 4" on each side to ensure privacy and eliminate light gap.)	
For height, measure from a point 2 1/2	

inches above the window trim to either the sill or floor:	
Measure the area available for stackback: (Window coverings associate will compute stackback needed to determine how your blinds will clear the window/door opening.)	

Room Location:	
Measure Area to be Covered	Inches
Measure Width of Window/Door: (Add 4" on each side to ensure privacy and eliminate light gap.)	
For height, measure from a point 2 1/2 inches above the window trim to either the sill or floor:	
Measure the area available for stackback: (Window coverings associate will compute stackback needed to determine how your blinds will clear the window/door opening.)	

Room Location:	
Measure Area to be Covered	Inches
Measure Width of Window/Door: (Add 4" on each side to ensure privacy and eliminate light gap.)	
For height, measure from a point 2 1/2 inches above the window trim to either the sill or floor:	
Measure the area available for stackback: (Window coverings associate will compute stackback needed to determine how your blinds will clear the window/door opening.)	